



Notes & Specifications

- Perimeter & Guy ropes - Combination rope 18mm dia 6 - strand wire strand (H+9/0,80)
Braided nylon IWRC
- Internal ropes - Combination rope 18mm dia 6 - strand wire strand (H+9/0,80)
Braided nylon FC
- Rope Connections - Aluminium magnesium alloy ferrules to DIN 1725.
- Central Mast - 5" diameter seamless stainless steel pipe with a 3.5mm wall, to ASTM A312, 304L
- Dome - Machined from solid Aluminium with stainless steel U - bolts to position the rope
- Foundations - Manufactured from Hot dip galvanised 43A grade mild steel, fabricated in accordance with Lloyds international spec.
Finish to EN 1461
- Turnbuckles - 1"UNC rigging screw proof loaded to 4400kg
- Bow shackles - Green pin bow shackle 3/4" by 7/8" proof loaded to 9500kg



Drawing Title :- Active range - Component list

Drawn By :- P Will

Quantity per set :- N/A

Revision No :- 2

File Name :- active4000 parts list.dwg

Date :- 16/04/2007

Scale :- 1:1

Tayplay UK Ltd.
Unit 14b Riverview Business Park,
Friarton Road, Perth, PH2 8DF
www.tayplay.com
tel:- 01738 449 084
fax:- 01738 449 094